LED Light

MODEL: BTL 2400

 Lumen Output
 Lifetime
 Wattage
 Replaces
 Warranty

 2371 lm
 50,000 hrs
 33
 150-175 MH / HPS
 3 years / 5 years optional

RoHS


CE



Another great product from Brightview Lighting, the BTL series of street lights offer LED technology at prices much lower than LED fixtures. For use in existing fixtures or new, these lamps are on an

E40/mogul screw in base just like a normal street light. Easily changed and easily installed.

New LED technology allows us to present products with increased light outputs, adding to that all of the benefits of LED technology: long life, low energy usage, semi directed light, dark sky compliant, clean clear light that works well with motion sensors.



FITS MOST:

- Street Light Cobra Head
- Wall Pack
- Cake Box
- Wall Washers
- Holophane
- Shoebox
- and more

New Fixtures also available special for these lamps

- Check existing fixtures for size and lens profile
- Light is projected from one side, lamp may be suitable for only some base up, base down applications
- Available in 12V versions, works well in solar packages



Power	
Input Voltage:	AC 85~264V/12VDC/24VDC
Power Factor:	83%
Calculated System Consumption:	32W
Other Configurations:	12V for solar, 277V, 480V

Light Output	
LED Luminous Efficiency	60 lm/w (Cree)
LED Lumens	2371lm(Tj=25)
Lamp's Efficiency (%)	>90%

Light Characteristics	
Color Temperature	Pure White:5,000 - 7,000
Color Index(CRI)	Ra>75
Light Source	Cree(1 Watt)
Light Distribution Curve/Beam	Asymmetric(Bat Wing)/Rectangular Beam
Beam Angle	The Horizontal Axis:120°, The Vertical Axis:60°

Operating Characteristics	
Junction Temperature(TJ)	70 ±10%(Ta=25)
Working Temperature	-20ºC~50ºC
Working Humidity	10%~90%RH
Working Life	>50,000Hrs

Dimensions	
Lamp Base	Mogul Base - E39/E40
The Dimensions(units:mm)	mm:265 x 90 h / in: 10 x 4 h
Net Weight(g)	Kg: 1.2 / Lbs: 2.5
IP Rating	IP60





Brightview Lighting LLC.

PO Box 246. Jenison, MI 49428 **phone:** 616-662-7330 **fax:** 866-781-7331 www.brightviewlighting.com